

Listing of Claims

This Listing of Claims replaces all prior versions, and listings, of claims in the above-captioned application.

1-6. (Cancelled)

7. (Previously Presented) A currency evaluation device for receiving a stack of currency bills and rapidly processing all the bills in the stack, the device comprising:

an input receptacle adapted to receive a stack of bills to be processed;

at least one output receptacle adapted to receive the bills after each of the bills have been processed;

a transport mechanism adapted to transport the bills, one at a time, from the input receptacle to the at least one output receptacle along a transport path in a transport direction;

a magnetic scanhead disposed adjacent to the transport path, the scanhead including an arrangement of a plurality of closely spaced magnetic sensors each adapted to detect the presence of a security thread within the bills, the arrangement of the plurality of closely spaced magnetic sensors being generally perpendicular to the transport direction, the scanhead being adapted to determine the location of the security thread within the bill;

a memory adapted to store master security thread location information corresponding to a plurality of denominations of currency bills; and

an evaluating unit adapted to determine the denomination of the currency bill when the determined security thread location favorably compares to the master security thread location information, the evaluating unit being adapted to generate an error signal when the determined security thread location does not favorably compare to master security thread location information.

8. (Original) The currency evaluation device of claim 7 wherein the plurality of sensors are linearly aligned within the scanhead.

9. (Original) The currency evaluation device of claim 8 wherein scanhead is disposed transverse to the document transport path.

10. (Previously Presented) The currency evaluation device of claim 9 wherein the spacing between adjacent ones of the plurality of sensors is about one millimeter.

11. (Cancelled)

12. (Original) The currency evaluation device of claim 7 wherein the transport mechanism is adapted to transport each of the bills such that a long edge of the bill is the leading edge of the bill.

13. (Previously Presented) The currency evaluation device of claim 7 wherein the bills are processed at a rate of at least 800 bills per minute.

14. (Previously Presented) A currency evaluation device for receiving a stack of currency bills and rapidly processing all the bills in the stack, the device comprising:

an input receptacle adapted to receive a stack of bills to be processed;

at least one output receptacle adapted to receive the bills after each of the bills have been processed;

a transport mechanism adapted to transport the bills, one at a time, from the input receptacle to the at least one output receptacle along a transport path in a transport direction;

a magnetic scanhead disposed adjacent to the transport path, the scanhead including an arrangement of a plurality of closely spaced magnetic sensors, the arrangement of the plurality of closely spaced magnetic sensors being generally perpendicular to the transport direction, each of the magnetic sensors being adapted to detect magnetic zone printing configuration information from each of the currency bills, each of the magnetic sensors adapted to detect the presence of a security thread within each of the bills, the magnetic scanhead being adapted to determine the location of a detected security thread within a currency bill;

a memory adapted to store master magnetic zone printing configuration information and master security thread location information; and

an evaluating unit adapted to determine the denomination of each of the bills by comparing the detected magnetic zone printing configuration information to the stored master

magnetic zone printing configuration information, the evaluating unit being adapted to authenticate each of the currency bills by comparing the determined security thread location to the stored master security thread location information.

15. (Original) The currency evaluation device of claim 14 wherein the plurality of sensors are linearly aligned within the scanhead.

16. (Original) The currency evaluation device of claim 15 wherein scanhead is disposed transverse to the document transport path.

17. (Previously Presented) The currency evaluation device of claim 16 wherein the spacing between adjacent ones of the plurality of sensors is about one millimeter.

18. (Cancelled)

19. (Original) The currency evaluation device of claim 14 wherein the transport mechanism is adapted to transport each of the bills such that a long edge of the bill is the leading edge of the bill.

20. (Previously Presented) The currency evaluation device of claim 14 wherein the bills are processed at a rate of at least 800 bills per minute.

21. (Previously Presented) A currency evaluation device for processing different types of currency bills including currency from different countries

an input receptacle adapted to receive a stack of bills to be processed;

at least one output receptacle adapted to receive the bills after each of the bills have been processed;

a transport mechanism adapted to transport the bills, one at a time, from the input receptacle to the at least one output receptacle along a transport path in a transport direction;

a magnetic scanhead disposed adjacent to the transport path, the scanhead including an arrangement of a plurality of closely spaced magnetic sensors, the arrangement of the plurality of

closely spaced magnetic sensors being generally perpendicular to the transport direction, each of the magnetic sensors being adapted to detect the presence of a security thread within each of the bills, the magnetic scanhead being adapted to determine the location of the detected security thread within a bill;

a memory adapted to store a plurality of master security thread information corresponding to a plurality of types of currency, the master security thread information defining a predetermined number of security thread locations for each of the plurality of currency types, the predetermined number corresponding to the number of denominations of bills in a particular currency type; and

an evaluating unit adapted to process each of the bills by comparing the determined security thread location to the master security thread location information corresponding to the type of currency, the evaluating unit being adapted to generate an error signal when the determined security thread location information does not favorably compare to one of the security locations for the particular currency type specified by the user.

22. (Previously Presented) The currency processing device of claims 21 wherein the evaluating unit is adapted to determine the type of currency being processed from among a plurality of currency types, the plurality of currency types corresponding to currency issued by a plurality of countries.

23. (Previously Presented) The currency processing device of claim 21 further comprising a user interface adapted to receive information from a user of the currency evaluation device specifying the type of currency to be processed.

24. (Previously Presented) The currency processing device of claim 21 wherein the plurality of sensors are linearly aligned within the scanhead.

25. (Previously Presented) The currency processing device of claim 24 wherein the scanhead is disposed transverse to the document transport path.

26. (Previously Presented) The currency processing device of claim 25 wherein the spacing between adjacent ones of the plurality of sensors is about one millimeter.

27. (Cancelled)

28. (Previously Presented) The currency processing device of claim 21 wherein the transport mechanism is adapted to transport each of the bills such that a long edge of the bill is the leading edge of the bill.

29. (Previously Presented) The currency processing device of claim 21 wherein the bills are evaluated at a rate of at least 800 bills per minute.

30-77. (Cancelled)

78. (Previously Presented) A currency evaluation device adapted to receive a currency bill having a magnetic attribute and processing the currency bill, the device comprising:
an inlet adapted to receive a currency bill to be processed;
an output receptacle adapted to receive the bill after the bill has been processed;
a transport mechanism adapted to transport the bill from the inlet to the output receptacle along a transport path in a transport direction such that the long edge of the bill is the leading edge of the bill;

a magnetic scanhead disposed adjacent to the transport path, the scanhead including a plurality of linearly aligned and closely spaced magnetic sensors, the plurality of linearly aligned and closely spaced magnetic sensors being linearly aligned generally perpendicular to the transport direction, the scanhead being adapted to detect the presence of a magnetic attribute of the bill when the magnetic attribute has a leading edge dimension greater than about one millimeter, the plurality of magnetic sensors covering a substantial portion of a long dimension of the bill, the scanhead being adapted to retrieve characteristic magnetic information from the currency bill, the scanhead being disposed transverse the transport path;

a memory adapted to store master magnetic characteristic information corresponding to a plurality of types of currency bills; and

an evaluating unit adapted to process the currency bill by comparing the retrieved magnetic characteristic information to the stored master magnetic characteristic information, the evaluating unit being adapted to generate an error signal when the retrieved characteristic magnetic information does not favorably compare to the stored master magnetic characteristic information.

79-80. (Cancelled)

81. (Previously Presented) The currency evaluation device of claim 78 wherein the spacing between adjacent sensors is less than about five millimeters.

82. (Previously Presented) The currency evaluation device of claim 78 wherein the spacing between adjacent sensors is less than about four millimeters.

83. (Previously Presented) The currency evaluation device of claim 78 wherein the spacing between adjacent sensors is less than about three millimeters.

84. (Previously Presented) The currency evaluation device of claim 78 wherein the spacing between adjacent sensors is less than about two millimeters.

85. (Previously Presented) The currency evaluation device of claim 78 wherein the spacing between adjacent sensors is about one millimeter.

86. (Cancelled)

87. (Previously Presented) The currency evaluation device of claim 78 wherein the spacing between adjacent sensors is about one-half millimeter.

88. (Original) The currency evaluation device of claim 78 wherein the transport mechanism is adapted to transport each of the bills such that a long edge of the bill is the leading edge of the bill.

89. (Previously Presented) The currency evaluation device of claim 78 wherein the bills are processed at a rate of at least 800 bills per minute.

90-145. (Cancelled)

146. (Presently Amended) A currency evaluation device adapted to receive a stack of currency bills and rapidly processing all the bills in the stack including bills having a magnetic attribute, the device comprising:

an input receptacle adapted to receive a stack of bills to be ~~evaluated~~ processed;

at least one output receptacle adapted to receive the bills after each of the bills have been ~~evaluated~~ processed;

a transport mechanism adapted to transport the bills, one at a time, from the input receptacle past ~~an evaluation region~~ a magnetic scanhead to the at least one output receptacle along a transport path, the transport mechanism being adapted to transport bills such that their narrow dimension is parallel to the direction of transport;

~~a magnetic scanhead disposed adjacent to the bill evaluation region~~, the scanhead including an arrangement of a plurality of closely spaced magnetic sensors each adapted to detect the presence of a magnetic attribute of currency bills, the arrangement of the plurality of closely spaced magnetic sensors being generally perpendicular to the direction of transport, the plurality of magnetic sensors covering a substantial portion of a long dimension of the currency bills, the scanhead being adapted to retrieve magnetic characteristic information from a passing currency bill;

a memory adapted to store master magnetic characteristic information corresponding to a plurality of types of currency bills; and

~~an evaluating unit adapted to process the currency bill by comparing~~ a processor programmed to compare the retrieved magnetic characteristic information to the stored master magnetic characteristic information, ~~the evaluating unit being adapted and~~ to generate an error signal when the retrieved magnetic characteristic information does not favorably compare to the stored master magnetic characteristic information.

147. (Previously Presented) The currency evaluation device of claim 146 wherein the plurality of magnetic sensors are linearly aligned and the spacing between adjacent magnetic sensors is less than about one millimeter.

148. (Presently Amended) A currency evaluation device for receiving a stack of currency bills and rapidly processing all the bills in the stack including bills having a magnetic attribute, the device comprising:

an input receptacle adapted to receive a stack of bills to be ~~evaluated~~ processed;

at least one output receptacle adapted to receive the bills after each of the bills have been ~~evaluated~~ processed;

a transport mechanism adapted to transport the bills in a transport direction, one at a time, from the input receptacle past ~~an evaluation region~~ a magnetic scanhead to the at least one output receptacle along a transport path, the transport mechanism being adapted to transport bills such that a wide edge of the bills is the leading edge of the bills;

~~a magnetic scanhead disposed adjacent to the bill evaluation region~~, the scanhead including an arrangement of at least two closely spaced magnetic sensors each adapted to detect the presence of a magnetic attribute of currency bills, the arrangement of the at least two closely spaced magnetic sensors being generally perpendicular to the transport direction, the at least two magnetic sensors being adapted to scan a substantially continuous segment of each of the bills, the substantially continuous segment being parallel to the ~~narrow~~ wide edge of the currency bills, the scanhead being adapted to retrieve magnetic characteristic information from the currency bill;

a memory adapted to store master magnetic characteristic information corresponding to a plurality of types of currency bills; and

~~an evaluating unit adapted to process the currency bill by comparing~~ a processor programmed to compare the retrieved magnetic characteristic information to the stored master magnetic characteristic information, ~~the evaluating unit being adapted and~~ to generate an error signal when the retrieved magnetic characteristic information does not favorably compare to the stored master magnetic characteristic information.

149. (Cancelled)

150. (Previously Presented) The currency evaluation device of claim 7, wherein a gap separates each of the plurality of closely spaced magnetic sensors from an adjacent one of the plurality of closely spaced magnetic sensors, the gap being about one-half millimeter.

151. (Previously Presented) The currency evaluation device of claim 7, wherein the plurality of closely spaced magnetic sensors have a center to center spacing of about five millimeters with each adjacent one of the plurality of closely spaced magnetic sensors.

152. (Cancelled)

153. (Previously Presented) The currency evaluation device of claim 14, wherein a gap separates each of the plurality of closely spaced magnetic sensors from an adjacent one of the plurality of closely spaced magnetic sensors, the gap being about one-half millimeter.

154. (Previously Presented) The currency evaluation device of claim 14, wherein the plurality of closely spaced magnetic sensors have a center to center spacing of about five millimeters with each adjacent one of the plurality of closely spaced magnetic sensors.

155. (Cancelled)

156. (Previously Presented) The currency evaluation device of claim 21, wherein a gap separates each of the plurality of closely spaced magnetic sensors from an adjacent one of the plurality of closely spaced magnetic sensors, the gap being about one-half millimeter.

157. (Previously Presented) The currency evaluation device of claim 21, wherein the plurality of closely spaced magnetic sensors have a center to center spacing of about five millimeters with each adjacent one of the plurality of closely spaced magnetic sensors.

158. (Cancelled)

159. (Previously Presented) The currency evaluation device of claim 78, wherein the plurality of linearly aligned and closely spaced magnetic sensors have a center to center spacing of about five millimeters with each adjacent one of the plurality of linearly aligned and closely spaced magnetic sensors.

160. (Cancelled)

161. (Previously Presented) The currency evaluation device of claim 146, wherein a gap separates each of the plurality of closely spaced magnetic sensors from an adjacent one of the plurality of closely spaced magnetic sensors, the gap being about one millimeter.

162. (Previously Presented) The currency evaluation device of claim 146, wherein a gap separates each of the plurality of closely spaced magnetic sensors from an adjacent one of the plurality of closely spaced magnetic sensors, the gap being about one-half millimeter.

163. (Previously Presented) The currency evaluation device of claim 146, wherein the plurality of closely spaced magnetic sensors have a center to center spacing of about five millimeters with each adjacent one of the plurality of closely spaced magnetic sensors.

164. (Cancelled)

165. (Previously Presented) The currency evaluation device of claim 148, wherein a gap separates the at least two closely spaced magnetic sensors, the gap being about one millimeter.

166. (Previously Presented) The currency evaluation device of claim 148, wherein a gap separates the at least two closely spaced magnetic sensors, the gap being about one-half millimeter.

167. (Previously Presented) The currency evaluation device of claim 148, wherein the at least two closely spaced magnetic sensors have a center to center spacing of about five millimeters.

168. (Cancelled)

169. (Presently Amended) A currency evaluation device adapted to receive a currency bill having a magnetic attribute and processing the currency bill, the device comprising:

an inlet adapted to receive a currency bill to be processed;

an output receptacle adapted to receive the bill after the bill has been processed;

a transport mechanism adapted to transport the bill from the inlet to the output receptacle along a transport path in a transport direction such that the long edge of the bill is the leading edge of the bill;

a magnetic scanhead disposed adjacent to the transport path, the scanhead including a plurality of linearly aligned magnetic sensors, the plurality of linearly aligned magnetic sensors being linearly aligned generally perpendicular to the transport direction, the scanhead being adapted to detect the presence of a magnetic attribute of the bill when the magnetic attribute has a leading edge dimension greater than about one millimeter, the plurality of magnetic sensors covering a substantial portion of a long dimension of the bill, the spacing between adjacent magnetic sensors being less than about one millimeter, the scanhead being adapted to retrieve characteristic magnetic information from the currency bill, the scanhead being disposed generally transverse the transport ~~path~~ direction;

a memory adapted to store master magnetic characteristic information corresponding to a plurality of types of currency bills; and

~~an evaluating unit adapted to process the currency bill by comparing a processor~~
programmed to compare the retrieved magnetic characteristic information to the stored master magnetic characteristic information, ~~the evaluating unit being adapted and~~ and to generate an error

signal when the retrieved characteristic magnetic information does not favorably compare to the stored master magnetic characteristic information.

170. (Previously Presented) The currency evaluation device of claim 169, wherein each of the plurality of magnetic sensors is a non-inductive sensor.

171. (Previously Presented) The currency evaluation device of claim 169, wherein each of the plurality of magnetic sensors is a magnetoresistive sensor.

172. (Presently Amended) A currency evaluation device for receiving a stack of currency bills and rapidly processing all the bills in the stack including bills having a magnetic attribute, the device comprising:

an input receptacle adapted to receive a stack of bills to be ~~evaluated~~ processed;

at least one output receptacle adapted to receive the bills after each of the bills have been ~~evaluated~~ processed;

a transport mechanism adapted to transport the bills in a transport direction, one at a time, from the input receptacle past ~~an evaluation region~~ a magnetic scanhead to the at least one output receptacle along a transport path, the transport mechanism being adapted to transport bills such that a wide edge of the bills is the leading edge of the bills;

~~a magnetic scanhead disposed adjacent to the bill evaluation region~~, the scanhead including an arrangement of at least two magnetic sensors each adapted to detect the presence of a magnetic attribute of currency bills, the arrangement of the at least two magnetic sensors being generally perpendicular to the transport direction, the at least two magnetic sensors being adapted to scan a substantially continuous segment of each of the bills, the spacing between the at least two magnetic sensors being less than about one millimeter, the substantially continuous segment being generally parallel to the ~~narrow~~ wide edge of the currency bills, the scanhead being adapted to retrieve magnetic characteristic information from the currency bill;

a memory adapted to store master magnetic characteristic information corresponding to a plurality of types of currency bills; and

~~an evaluating unit adapted to process the currency bill by comparing~~ a processor programmed to compare the retrieved magnetic characteristic information to the stored master

magnetic characteristic information, ~~the evaluating unit being adapted and~~ to generate an error signal when the retrieved magnetic characteristic information does not favorably compare to the stored master magnetic characteristic information.

173. (Previously Presented) The currency evaluation device of claim 172, wherein each of the at least two magnetic sensors is a non-inductive sensor.

174. (Previously Presented) The currency evaluation device of claim 172, wherein each of the at least two magnetic sensors is a magnetoresistive sensor.

175. (Presently Amended) A currency evaluation device for receiving a stack of currency bills and rapidly processing all the bills in the stack, the device comprising:

an input receptacle adapted to receive a stack of bills to be processed;

at least one output receptacle adapted to receive the bills after each of the bills have been processed;

a transport mechanism adapted to transport the bills, one at a time, from the input receptacle to the at least one output receptacle along a transport path in a transport direction;

a magnetic scanhead disposed adjacent to the transport path, the scanhead including an arrangement of a plurality of linearly aligned magnetic sensors each adapted to detect the presence of a security thread within the bills, the arrangement of the plurality of magnetic sensors being generally perpendicular to the transport direction, the spacing between adjacent magnetic sensors being less than about one millimeter, the scanhead being adapted to determine the location of the security thread within the bill;

a memory adapted to store master security thread location information corresponding to a plurality of denominations of currency bills; and

~~an evaluating unit adapted a processor programmed~~ to determine the denomination of the currency bill when the determined security thread location favorably compares to the master security thread location information, ~~the evaluating unit processor being adapted programmed~~ to generate an error signal when the determined security thread location does not favorably compare to master security thread location information.

176. (Previously Presented) The currency evaluation device of claim 175, wherein each of the plurality of magnetic sensors is a non-inductive sensor.

177. (Previously Presented) The currency evaluation device of claim 175, wherein each of the plurality of magnetic sensors is a magnetoresistive sensor.

178. (Presently Amended) A currency evaluation device adapted to receive a stack of currency bills and rapidly processing all the bills in the stack including bills having a magnetic attribute, the device comprising:

an input receptacle adapted to receive a stack of bills to be ~~evaluated~~ processed;

at least one output receptacle adapted to receive the bills after each of the bills have been ~~evaluated~~ processed:

a transport mechanism adapted to transport the bills, one at a time, from the input receptacle past ~~an evaluation region~~ a magnetic scanhead to the at least one output receptacle along a transport path, the transport mechanism being adapted to transport bills such that their narrow dimension is parallel to the direction of transport;

~~a magnetic scanhead disposed adjacent to the bill evaluation region~~, the scanhead including an arrangement of a plurality of linearly aligned magnetic sensors each adapted to detect the presence of a magnetic attribute of currency bills, the arrangement of the plurality of magnetic sensors being generally perpendicular to the direction of transport, the plurality of magnetic sensors covering a substantial portion of a long dimension of the currency bills, the spacing between adjacent magnetic sensors being less than about one millimeter, the scanhead being adapted to retrieve magnetic characteristic information from a passing currency bill;

a memory adapted to store master magnetic characteristic information corresponding to a plurality of types of currency bills; and

~~an evaluating unit adapted to process the currency bill by comparing~~ a processor programmed to compare the retrieved magnetic characteristic information to the stored master magnetic characteristic information, ~~the evaluating unit being adapted and~~ to generate an error signal when the retrieved magnetic characteristic information does not favorably compare to the stored master magnetic characteristic information.

179. (Previously Presented) The currency evaluation device of claim 178, wherein each of the plurality of magnetic sensors is a non-inductive sensor.

180. (Previously Presented) The currency evaluation device of claim 178, wherein each of the plurality of magnetic sensors is a magnetoresistive sensor.

181. (Presently Amended) A currency evaluation device adapted to receive a currency bill having a magnetic attribute and processing the currency bill, the device comprising:

an inlet adapted to receive a currency bill to be processed;

an output receptacle adapted to receive the bill after the bill has been processed;

a transport mechanism adapted to transport the bill from the inlet to the output receptacle along a transport path in a transport direction such that the long edge of the bill is the leading edge of the bill;

a magnetic scanhead disposed adjacent to the transport path, the scanhead including a plurality of linearly aligned and closely spaced non-inductive magnetic sensors, the plurality of linearly aligned and closely spaced non-inductive magnetic sensors being linearly aligned generally perpendicular to the transport direction, the scanhead being adapted to detect the presence of a magnetic attribute of the bill when the magnetic attribute has a leading edge dimension greater than about one millimeter, the plurality of magnetic sensors covering a substantial portion of a long dimension of the bill, the scanhead being adapted to retrieve characteristic magnetic information from the currency bill, the scanhead being disposed transverse the transport path;

a memory adapted to store master magnetic characteristic information corresponding to a plurality of types of currency bills; and

~~an evaluating unit adapted to process the currency bill by comparing a processor~~
programmed to compare the retrieved magnetic characteristic information to the stored master magnetic characteristic information, ~~the evaluating unit being adapted and~~ to generate an error signal when the retrieved characteristic magnetic information does not favorably compare to the stored master magnetic characteristic information.

182. (Presently Amended) A currency evaluation device for receiving a stack of currency bills and rapidly processing all the bills in the stack including bills having a magnetic attribute, the device comprising:

an input receptacle adapted to receive a stack of bills to be evaluated;

at least one output receptacle adapted to receive the bills after each of the bills have been evaluated;

a transport mechanism adapted to transport the bills in a transport direction, one at a time, from the input receptacle past ~~an evaluation region~~ a magnetic scanhead to the at least one output receptacle along a transport path, the transport mechanism being adapted to transport bills such that a wide edge of the bills is the leading edge of the bills;

~~a magnetic scanhead disposed adjacent to the bill evaluation region~~, the scanhead including an arrangement of at least two closely spaced non-inductive magnetic sensors each adapted to detect the presence of a magnetic attribute of currency bills, the arrangement of the at least two closely spaced non-inductive magnetic sensors being generally perpendicular to the transport direction, the at least two magnetic sensors being adapted to scan a substantially continuous segment of each of the bills, the substantially continuous segment being parallel to the ~~narrow~~ wide edge of the currency bills, the scanhead being adapted to retrieve magnetic characteristic information from the currency bill;

a memory adapted to store master magnetic characteristic information corresponding to a plurality of types of currency bills; and

~~an evaluating unit adapted to process the currency bill by comparing~~ a processor programmed to compare the retrieved magnetic characteristic information to the stored master magnetic characteristic information, ~~the evaluating unit being adapted and~~ to generate an error signal when the retrieved magnetic characteristic information does not favorably compare to the stored master magnetic characteristic information.

183. (Presently Amended) A currency evaluation device for receiving a stack of currency bills and rapidly processing all the bills in the stack, the device comprising:

an input receptacle adapted to receive a stack of bills to be processed;

at least one output receptacle adapted to receive the bills after each of the bills have been processed;

a transport mechanism adapted to transport the bills, one at a time, from the input receptacle to the at least one output receptacle along a transport path in a transport direction;

a magnetic scanhead disposed adjacent to the transport path, the scanhead including an arrangement of a plurality of closely spaced non-inductive magnetic sensors, the arrangement of the plurality of closely spaced non-inductive magnetic sensors being generally perpendicular to the transport direction, each of the magnetic sensors being adapted to detect magnetic zone printing configuration information from each of the currency bills, each of the magnetic sensors adapted to detect the presence of a security thread within each of the bills, the magnetic scanhead being adapted to determine the location of a detected security thread within a currency bill;

a memory adapted to store master magnetic zone printing configuration information and master security thread location information; and

~~an evaluating unit adapted~~ a processor programmed to determine the denomination of each of the bills by comparing the detected magnetic zone printing configuration information to the stored master magnetic zone printing configuration information, ~~the evaluating unit being adapted~~ the processing being programmed to authenticate each of the currency bills by comparing the determined security thread location to the stored master security thread location information.

184. (Previously Presented) The currency evaluation device of claim 183, wherein the plurality of magnetic sensors are linearly aligned and the spacing between adjacent magnetic sensors is less than about one millimeter.

185. (Previously Presented) The currency evaluation device of claim 183, wherein each of the plurality magnetic sensors is a magnetoresistive sensor.

186. (Presently Amended) A currency evaluation device adapted to receive a currency bill having a magnetic attribute and processing the currency bill, the device comprising:
an inlet adapted to receive a currency bill to be processed;
an output receptacle adapted to receive the bill after the bill has been processed;

a transport mechanism adapted to transport the bill from the inlet to the output receptacle along a transport path in a transport direction such that the long edge of the bill is the leading edge of the bill;

a magnetic scanhead disposed adjacent to the transport path, the scanhead including a plurality of linearly aligned and closely spaced magnetoresistive magnetic sensors, the plurality of linearly aligned and closely spaced magnetoresistive magnetic sensors being linearly aligned generally perpendicular to the transport direction, the scanhead being adapted to detect the presence of a magnetic attribute of the bill when the magnetic attribute has a leading edge dimension greater than about one millimeter, the plurality of magnetic sensors covering a substantial portion of a long dimension of the bill, the scanhead being adapted to retrieve characteristic magnetic information from the currency bill, the scanhead being disposed transverse the transport path;

a memory adapted to store master magnetic characteristic information corresponding to a plurality of types of currency bills; and

~~an evaluating unit adapted to process the currency bill by comparing a processor~~
programmed to compare the retrieved magnetic characteristic information to the stored master magnetic characteristic information, ~~the evaluating unit being adapted~~ and to generate an error signal when the retrieved characteristic magnetic information does not favorably compare to the stored master magnetic characteristic information.

187. (Presently Amended) A currency evaluation device for receiving a stack of currency bills and rapidly processing all the bills in the stack including bills having a magnetic attribute, the device comprising:

an input receptacle adapted to receive a stack of bills to be ~~evaluated~~ processed;

at least one output receptacle adapted to receive the bills after each of the bills have been ~~evaluated~~ processed;

a transport mechanism adapted to transport the bills in a transport direction, one at a time, from the input receptacle past ~~an evaluation region~~ a magnetic scanhead to the at least one output receptacle along a transport path, the transport mechanism being adapted to transport bills such that a wide edge of the bills is the leading edge of the bills;

~~a magnetic scanhead disposed adjacent to the bill evaluation region~~, the scanhead including an arrangement of at least two closely spaced magnetoresistive magnetic sensors each adapted to detect the presence of a magnetic attribute of currency bills, the arrangement of the at least two closely spaced magnetoresistive magnetic sensors being generally perpendicular to the transport direction, the at least two magnetic sensors being adapted to scan a substantially continuous segment of each of the bills, the substantially continuous segment being generally parallel to the narrow wide edge of the currency bills, the scanhead being adapted to retrieve magnetic characteristic information from the currency bill;

a memory adapted to store master magnetic characteristic information corresponding to a plurality of types of currency bills; and

~~an evaluating unit adapted to process the currency bill by comparing~~ a processor programmed to compare the retrieved magnetic characteristic information to the stored master magnetic characteristic information, ~~the evaluating unit being adapted and~~ to generate an error signal when the retrieved magnetic characteristic information does not favorably compare to the stored master magnetic characteristic information.

188. (Presently Amended) A currency evaluation device for processing different types of currency bills including currency from different countries, the device comprising:

an input receptacle adapted to receive a stack of bills to be processed;

at least one output receptacle adapted to receive the bills after each of the bills have been processed;

a transport mechanism adapted to transport the bills, one at a time, from the input receptacle to the at least one output receptacle along a transport path in a transport direction;

a magnetic scanhead disposed adjacent to the transport path, the scanhead including an arrangement of a plurality of closely spaced magnetoresistive magnetic sensors, the arrangement of the plurality of closely spaced magnetoresistive magnetic sensors being generally perpendicular to the transport direction, each of the magnetic sensors being adapted to detect the presence of a security thread within each of the bills, the magnetic scanhead being adapted to determine the location of the detected security thread within a bill;

a memory adapted to store a plurality of master security thread information corresponding to a plurality of types of currency, the master security thread information defining

a predetermined number of security thread locations for each of the plurality of currency types, the predetermined number corresponding to the number of denominations of bills in a particular currency type; and

~~an evaluating unit adapted to process each of the bills by comparing a processor programmed to compare~~ the determined security thread location to the master security thread location information corresponding to the type of currency, ~~the evaluating unit being adapted and~~ to generate an error signal when the determined security thread location information does not favorably compare to one of the security locations for the particular currency type specified by the user.

189. (Previously Presented) The currency evaluation device of claim 188, wherein the plurality of magnetic sensors are linearly aligned and the spacing between adjacent magnetic sensors is less than about one millimeter.

190. (New) The currency evaluation device of claim 7 wherein the plurality of magnetic sensors collectively extend at least about 79.5 millimeters in a direction transverse to the transport direction.

191. (New) The currency evaluation device of claim 7 wherein the plurality of magnetic sensors collectively extend at least about 159.5 millimeters in a direction transverse to the transport direction.

192. (New) The currency evaluation device of claim 78 wherein the plurality of magnetic sensors collectively extend at least about 79.5 millimeters in a direction transverse to the transport direction.

193. (New) The currency evaluation device of claim 78 wherein the plurality of magnetic sensors collectively extend at least about 159.5 millimeters in a direction transverse to the transport direction.

194. (New) The currency evaluation device of claim 146 wherein the arrangement of the plurality of magnetic sensors extends at least about 79.5 millimeters in a direction transverse to the direction of transport.

195. (New) The currency evaluation device of claim 146 wherein the arrangement of the plurality of magnetic sensors extends at least about 159.5 millimeters in a direction transverse to the direction of transport.

196. (New) The currency evaluation device of claim 148 wherein the plurality of magnetic sensors collectively extend at least about 79.5 millimeters in a direction transverse to the transport direction.

197. (New) The currency evaluation device of claim 148 wherein the plurality of magnetic sensors collectively extend at least about 159.5 millimeters in a direction transverse to the transport direction.

198. (New) The currency evaluation device of claim 169 wherein the plurality of magnetic sensors collectively extend at least about 79.5 millimeters in a direction transverse to the transport direction.

199. (New) The currency evaluation device of claim 169 wherein the plurality of magnetic sensors collectively extend at least about 159.5 millimeters in a direction transverse to the transport direction.

200. (New) The currency evaluation device of claim 172 wherein the magnetic sensors collectively extend at least about 79.5 millimeters in a direction transverse to the transport direction.

201. (New) The currency evaluation device of claim 172 wherein the magnetic sensors collectively extend at least about 159.5 millimeters in a direction transverse to the transport direction.

202. (New) The currency evaluation device of claim 180 wherein the arrangement of the plurality of magnetic sensors extends at least about 79.5 millimeters in a direction transverse to the direction of transport.

203. (New) The currency evaluation device of claim 180 wherein the arrangement of the plurality of magnetic sensors extends at least about 159.5 millimeters in a direction transverse to the direction of transport.

204. (New) The currency evaluation device of claim 187 wherein the magnetic sensors collectively extend at least about 79.5 millimeters in a direction transverse to the transport direction.

205. (New) The currency evaluation device of claim 187 wherein the magnetic sensors collectively extend at least about 159.5 millimeters in a direction transverse to the transport direction.